



Fondo


1. Dimensions / Weight




FONDO PP 4L
weight: 4.60 kg



FONDO PP 4L ARM
weight: 5.40 kg



FONDO PP CFS-ROD
weight: 5.80 kg



FONDO PP HOCKER
weight: 9.00 kg

2. Materials / Version

2.1. Frame

4-leg frame (4L) – made of $\varnothing 18 \times 2.0$ mm steel tube,

4-leg frame with integrated armrests (4L-ARM) – made of $\varnothing 18 \times 2.0$ mm steel tube

Sled frame (CFS ROD) – made of $\varnothing 11$ mm steel rod,

HOCKER 4-leg frame – made of – $\varnothing 18 \times 2.0$ mm steel tube and $\varnothing 10$ mm steel rod for footrest.

Finish options:

- powder-coated in Jet black RAL 9005 colour (BL),
- powder-coated in White aluminium RAL 9006 colour (ALU),
- chromium plated (CR).

Stacking:

4L – up to 6 pieces,
4L ARM – up to 3 pieces,
CFS ROD – up to 8 pieces,
CFS ROD SEAT PLUS – up to 4 pieces,
HOCKER – up to 6 pieces
Stacking of FONDO SEAT PLUS versions recommended with stacking cushion.
Universal chair cart available.

2.2. Glides

4L / 4L ARM version:

Glides for soft floors (GB) as standard or with felt for hard floors (GBF) as an option.

CFS-ROD version:

Transparent glides for soft floors (GT) as standard or with felt for hard floors (GTF) as an option.

HOCKER 4-leg version:

Glides for soft floors (GB) as standard or with felt for hard floors (GBPF) as an option.

2.3. Seat and backrest

Plastic shell – made of polypropylene (PP),

Plastic shell with upholstered seat pad

(SEAT-PLUS) – seat pad made of 3-layer beech plywood, thickness 4.5 mm covered with foam, density 25 kg / m³, thickness 15 mm.

3. Packaging

4 pieces per box (assembled).

4. Technical regulations, approvals and quality marks for the chairs (for selected product configurations)

Durability certificate

REMODEX: EN 16139, EN 1728, EN 1022.

* Dimensions measured under load in accordance with the EN standard.