



Log pouf in flexible polyurethane foam fire retardant grade

Pouf Log imbottito in poliuretano flessibile ignifugo / Pouf Log mit feuerhemmendem, flexiblem Polyurethan gepolstert / Pouf Log rembourré avec polyuréthane ignifuge flexible / Puf Log tapizado en espuma de poliuretano flexible ignifugo

MATERIALS Materiali Materialien Matériaux Materiales	• SEAT - SEDUTA - SITZ - ASSISE - ASIENTO Upholstered in flexible expanding polyurethane, fire retardant (density 40 kg/m³, class 1 IM, Crib 5) Imbottita in poliuretano flessibile ignifugo (densità 40 kg/m³, classe 1 IM, Crib 5) / Polyurethanschaum, schwerentflammbar (Dichte 40 kg/m³, Klasse 1 IM, Crib 5) / Rembourré en polyuréthane souple, non feu (densité 40 kg/m³, classe 1 IM, Crib 5) / Tapizado con espuma de poliuretano flexible, ignifugo (densidad 40 kg/m³, clase 1 IM, Crib 5) FABRIC - TESSUTO - STOFF - TISSU - TEJIDO Cat. C - D - E - G - H20+H35 - H80+H90 FEET - PIEDINI - GLEITER - PATINS - TACOS In polyethylene, black In polietilene, nero / Polyethylen, schwarz / En polyéthylène, noir / De polietileno, negro
REGULATIONS AND CERTIFICATES Normative e Certificazioni Bestimmungen und Zertifikat Normatives et certifications Normativas y certificados	Conforming to: seat and back static load test EN 1728 - EN 16139, level L2 - extreme Conforme alla norma: carico statico sul sedile-schienale EN 1728 - EN 16139, livello L2 - estremo Conforming to: combined seat and back fatigue test, 200.000 cycles EN 1728 - EN 16139, level L2 - extreme Conforme alla norma: resistenza a fatica del sedile-schienale, 200.000 cicli EN 1728 - EN 16139, livello L2 - estremo