


# Bizzi

# Technical description

## 1. Dimensions/Weight



BIZZI TS25 RTS FS


**BIZZI sample configuration**  
 Witch ST44 Base  
 and 3-D Armrests


Model	Dimensions (mm)														Weight (kg)
	A	B	C	D	E	F	G	H	J	K	L	I	M	N	
BIZZI TS25 RTS FS SH	410–525	405	450	475	1070–1260	470	580	655–725	710	—	644	—	—	—	15,4
BIZZI TS25 RTS FST SH	410–525	405–455	450	475	1070–1260	470	580	655–725	710	—	644	—	—	—	16,2

**A** – Seat height  
**B** – Seat depth  
**C** – Seat surface depth  
**D** – Seat width  
**E** – Overall height

**F** – Backrest width  
**G** – Backrest length  
**H** – Backrest height  
**J** – Base diameter  
**K** – Base width

**L** – Overall depth  
**I** – Headrest height  
**M** – Headrest width  
**N** – Headrest height



Armrests	Dimensions (mm)					Weight (kg)
	Z	Y	X	W	V	
GTP42	240	230	50	505	605	1,8
R15K	200–280	255	90	450–510	625–685	3

**Z** – Armrest height  
**Y** – Armrest length

**X** – Armrest width  
**W** – Internal width between armrests

**V** – External width between armrests

## 2. Materials/Versions

### 2.1. Base

#### Bases:

- Ø 710 mm five-star black polyamide (TS25),
- Ø 700 mm five-star polished aluminium with chrome effect (ST44-POL).

### 2.2. Castors

Ø 50 mm black plastic self-braking castors for soft floors (SH) as standard, or hard floors (SHH) as an option.

### 2.3. Mechanisms

#### FS synchronous mechanism – functions:

- free-floating – synchronous backrest and seat tilt,
- backrest tilt angle of 20° synchronised with the seat tilt angle of 11°,
- seat and backrest multi-lock in 5 positions,
- backrest tilt force adjustment with a knob,
- seat depth adjustment 50 mm – as an option (FST),

- Anti-Shock – a feature that controls chair backrest to avoid hitting user's back after releasing the lock,
- smooth height adjustment of chair with pneumatic gas lift.

### 2.4. Seat and backrest

#### Seat

Structure is made of 8-layer plywood, thickness 11.5 mm, covered with 2 layers of foam, front part, thickness 35, density 40 kg/m³, back part, thickness 15 mm, density 40 kg/m³ and profiled foam R-70.

#### Backrest

Structure is made of polypropylene (PP) covered with foam, thickness 50 mm, density 21 kg/m³. Backrest cover is made of black polypropylene (PP).

## 3. Armrests

**Fixed armrests** – made of black polypropylene (PP).

**3-D armrests** – made of steel powder-coated in Jet black RAL 9005 colour or chromium plated and glass fiber reinforced polyamide (PA + GF) with black polyurethane (PU) pads.

Adjustment range of the armrests: height 80 mm, side movement of the armrests 50 mm, forward/backward movement of the pad 70 mm.

## 4. Packaging

1 piece per box (unassembled), 10 pieces on pallet.

## 5. Technical regulations, approvals and quality marks for the chairs (for selected product configurations)

Remodex (durability certificate) – approvals compliant with: EN 1335 and EN 1022.

**Omega Ekspres SIA**

LV40003402577

Biroja adrese: Lāčplēša 125, LV-1003, Rīga

**[www.city-office.lv](http://www.city-office.lv)**

[info@city-office.lv](mailto:info@city-office.lv)