



# Espacio


## 1. Dimensions/Weight




**ESPACIO 4L**  
weight: 6.50 kg



**ESPACIO 4L-ARM**  
weight: 8.00 kg



**ESPACIO CFP**  
weight: 8.70 kg



**UNIVERSAL ROW CONNECTOR**  
weight: 0.95 kg

## 2. Materials/Versions

### 2.1. Frame

#### 2.1.1. Frame

4-leg frame (4L) – made of steel tube legs  $\varnothing 22 \times 2.0$  mm, supporting bars  $\varnothing 22 \times 2.5$  mm.

4-leg frame with armrests (4L-ARM) – made of steel tube  $\varnothing 22 \times 2.0$  mm, supporting bars  $\varnothing 22 \times 2.5$  mm.

Cantilever frame with armrests (CFP) – made of steel tube  $\varnothing 22 \times 2.5$  mm.

Finish options:

– chromium plated (CR).

Stacking – 4 pieces

#### 2.1.2. Click/link

##### UNIVERSAL ROW CONNECTOR

– dedicated to connect opposite rows of chairs,

– distance adjustment: 470–530 mm,

– fixing to the floor as an option,

– powder-coated in Jet black RAL 9005 (BL) colour.

##### ESPACIO ROW CONNECTOR RIGHT

– dedicated to connect opposite rows of chairs,

– distance between rows: 490 mm,

– fixing to the floor as an option,

– chromium plated finish.

### 2.2. Glides

#### 4-leg frame

Glides for soft floors (GB) as standard and for hard floors (GBF) as an option.

Self-levelling glides for soft floors (GBP) or hard floors (GBPF) both as an option – chair with self-levelling glides is approx. 20 mm higher.

#### Cantilever CFP frame

Glides for soft floors (GB) as standard or for hard floors (GBF) as an option.

### 2.3. Seat and backrest

Wooden shell (WOOD) – made of 6-layer beech plywood, thickness 9 mm.

#### Wooden shell with upholstered pad on seat

(SEAT-PLUS) – the structure of seat pad is made of 3-layer beech plywood, thickness 3.5 mm, covered with foam thickness 9 mm, density 35 kg/m<sup>3</sup>.

All versions available with stacking cushion made of beech plywood, thickness 5 mm, covered with foam, thickness 9 mm, density 21 kg/m<sup>3</sup> (as standard).

### 2.4. Armrests

Fixed armrests – integrated with the chair frame. Armrests caps made of solid beech wood, thickness 10 mm.

### 3. Packaging

4L/4L ARM: 4 pieces (assembled chair).

CFP: 3 pieces (assembled chair).

### 4. Technical regulations, approvals and quality marks for the chairs (for selected product configurations)

REMODEX – durability certificate: EN 16139, EN 1728, EN 1022.