




## 1. Dimensions / Weight




**FONDO PP 4L**  
weight: 4.60 kg



**FONDO PP 4L ARM**  
weight: 5.40 kg



**FONDO PP CFS-ROD**  
weight: 5.80 kg



**FONDO PP HOCKER**  
weight: 9.00 kg

## 2. Materials / Version

### 2.1. Frame

4-leg frame (4L) – made of  $\varnothing 18 \times 2.0$  mm steel tube,  
4-leg frame with integrated armrests (4L-ARM) – made of  $\varnothing 18 \times 2.0$  mm steel tube  
Sled frame (CFS ROD) – made of  $\varnothing 11$  mm steel rod,  
HOCKER 4-leg frame – made of –  $\varnothing 18 \times 2.0$  mm steel tube and  $\varnothing 10$  mm steel rod for footrest.

#### Finish options:

- powder-coated in Jet black RAL 9005 colour (BL),
- powder-coated in White aluminium RAL 9006 colour (ALU),
- chromium plated (CR).

### Stacking:

4L – up to 6 pieces,  
 4L ARM – up to 3 pieces,  
 CFS ROD – up to 8 pieces,  
 CFS ROD SEAT PLUS – up to 4 pieces,  
 HOCKER – up to 6 pieces  
 Stacking of FONDO SEAT PLUS versions recommended with stacking cushion.  
 Universal chair cart available.

### 2.2. Glides

#### 4L/4L ARM version:

Glides for soft floors (GB) as standard or with felt for hard floors (GBF) as an option.

#### CFS-ROD version:

Transparent glides for soft floors (GT) as standard or with felt for hard floors (GTF) as an option.

#### HOCKER 4-leg version:

Glides for soft floors (GB) as standard or with felt for hard floors (GBPF) as an option.

### 2.3. Seat and backrest

Plastic shell – made of polypropylene (PP),  
Plastic shell with upholstered seat pad (SEAT-PLUS) – seat pad made of 3-layer beech plywood, thickness 4.5 mm covered with foam, density 25 kg / m<sup>3</sup>, thickness 15 mm.

## 3. Technical regulations, approvals and quality marks for the chairs (for selected product configurations)

Durability certificate

REMODEX: EN 16139, EN 1728, EN 1022.

\*Dimensions measured under load in accordance with the EN standard.