



Loco II

1. Dimensions/Weight



LOCO-II 4L*
weight: 8.00 kg



LOCO-II-CLICK 4L*
weight: 8.00 kg

2. Materials/Versions

2.1. Frame

4-leg frame made of steel tubes $\varnothing 22 \times 1.5$ mm.

4-leg frame with CLICK – made of steel tubes $\varnothing 22 \times 1.5$ mm, with integrated metal link to connect chairs into rows available in the same finish as chair frame.

Finish options:

- powder-coated in White aluminium RAL 9006 colour (ALU),
- powder-coated in Jet black RAL 9005 colour (BL),
- chromium plated (CR).

Stacking: up to 4 pieces.

2.2. Glides

Glides for soft floors (GB) as standard or hard floors (GBF) as an option.

2.3. Seat and backrest

Seat

Structure is made of 5-layer beech plywood, thickness 7 mm, covered with foam thickness 60 mm, density 35 kg/m^3 .

Backrest

Structure is made of 6-layer beech plywood, thickness 8.5 mm. Front side of the backrest covered with foam thickness 30 mm, density 35 kg/m^3 . Back side of the backrest covered with foam thickness 10 mm, density 21 kg/m^3 .

2.4. Armrests

Fixed armrests – integrated with chair frame, armrest pads made of beech solid wood, variable thickness up to 26 mm, width 40 mm.
Finish options: stained wood (NF-xx**).

3. Packaging

2 pieces per box (assembled), 4 boxes on the pallet.

4. Technical regulations, approvals and quality marks for the chairs (for selected product configurations)

Remodex (durability certificate) – approvals compliant with:

EN 16139, EN 1728, EN 1022